



LedKoning

WARM WIT COB LED STRIP

384
LEDS P/M



Warm Wit






SPECIFICATIES



Dimbaar	Ja		
3M plakstrip over gehele lengte	Ja		
Garantie	2 jaar		
Op maat te knippen	Elke 4cm		
Aantal LED's p/m	384		
Type LED	COB		
Stralingshoek	180 graden		
Kleur	Warm Wit		
Kleurtemperatuur (Kelvin)	2700		
CRI	93.8		
Lichtsterkte (lumen) p/m	673.7		
Aantal branduren	50.000		
Voltage (DC)	24V		
Watt - vermogen p/m	8.36W		
Lumen per Watt	80.58		
Watt per LED	0,022		
Bescherming	IP20, IP65 of IP67		
Materiaal waterdichte bescherming (IP65/IP67)	Siliconen		
Achtergrond kleur strip (PCB)	Wit		
Plakstrip	IP20: 3M 300LSE	IP65: 3M VHB	P67: 3M VHB
Breedte led strip	IP20: 8mm	IP65: 10mm	IP67: 10mm
Dikte led strip	IP20: 1,7mm	IP65: 3,7mm	IP67: 3,7mm
Aansluiting begin	5.5x2.1 DC stekker type vrouw		
Aansluiting einde	5.5x2.1 DC stekker type man		

TECHNISCHE TEKENINGEN

IP20



IP65/67



IP20



IP65




IP67





1M COB WARM WIT- 384 LEDS P/M



Color Parameters:

Chromaticity Coordinate: $x=0.4633$ $y=0.4097$ / $u'=0.2651$ $v'=0.5275$
 CCT=2646K (Duv=-0.0006) Dominant WL:Ld =584.7nm Purity=62.1%
 Ratio:R=27.4% G=70.4% B=2.2% Peak WL:Lp=630.3nm FWHM=144.3nm
 Render Index:Ra=95.7 CRI=93.8

R1 =97	R2 =98	R3 =96	R4 =97	R5 =97	R6 =98	R7 =95
R8 =89	R9 =75	R10=93	R11=96	R12=90	R13=98	R14=97 R15=94

Photo Parameters:

Flux = 673.7 lm Eff. : 80.58 lm/W Fe = 2.494 W

Electrical parameters:

V = 23.997 V I = 0.3484 A P = 8.361 W PF = 1.000
 LEVEL:OUT WHITE:ANSI_2700K

Status: Integral T = 250 ms Ip = 51644 (79%)



CE CERTIFICAAT

Certificate of Conformity



AN XIN TESTING CERTIFICATION

Certification No. : ATT20092500369E
Applicant : Ledkoning
Address : Rietveldenweg 49D
 5222AP 's Hertogenbosch, The Netherlands
Manufacturer : Ledkoning
Address : Rietveldenweg 49D
 5222AP 's Hertogenbosch, The Netherlands
Product Description : COB LED Strip
 CBWWLS384-01M2420 ,CBWWLS384-02M2420,CBWWLS384-03M2420
 CBWWLS384-04M2420 ,CBWWLS384-05M2420,CBWWLS384-01M2465
 CBWWLS384-02M2465,CBWWLS384-03M2465,CBWWLS384-04M2465
 CBWWLS384-05M2465,CBHWLS384-01M2420, CBHWLS384-02M2420
 CBHWLS384-03M2420,CBHWLS384-04M2420,CBHWLS384-05M2420
Model : CBHWLS384-01M2465,CBHWLS384-02M2465,CBHWLS384-03M2465
 CBHWLS384-04M2465,CBHWLS384-05M2465,24KCB384-05M2420
 24KCB384-05M2465,30KCB384-05M2420,30KCB384-05M2465
 65KCB384-05M2420,65KCB384-05M2465,ROCB384-05M2420
 ROCB384-05M2465,GRCB384-05M2420,GRCB384-05M2465
 BLCB384-05M2420,BLCB384-05M2465
Trademark : N/A

The above products have been tested by us with listed standards and found in compliance with the Directive 2014/35/EU. It is possible to use CE marking to demonstrate the compliance with this Directive.

Test Standards	EN 55015: 2019
	EN 61547: 2009
	EN 61000-3-2:2019
	EN 61000-3-3: 2013+A1:2019

The certificate is based on a single evaluation of tested samples of above-mentioned product. It does not imply an assessment of the whole production and does not permit the use of the test laboratory logo.



Authorized Signer:

Kevin Liu/Manager
Sep. 27, 2020

Shenzhen An-Xin Testing Service Co., Ltd.

Room 402-405, Floor 4th, Building C, Yuxing Technology Industrial Park, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China
 ☎ 86-0755-23009643 ☎ 86-0755-23009643 🌐 <http://www.anxinlab.com/>

Adres: Rietveldenweg 49D, 5222AP 's Hertogenbosch
 Tel: +3173 704 1100
 E-mail: info@ledkoning.nl
 Website: www.ledkoning.nl