




LedKoning

BLAUW COB LED STRIP

384
LEDS P/M



Blauw






SPECIFICATIES


Dimbaar	Ja
3M plakstrip over gehele lengte	Ja
Garantie	2 jaar
Op maat te knippen	Elke 8,3 cm
Aantal LED's p/m	384
Type LED	COB
Stralingshoek	180 graden
Kleur	Blauw
Kleurtemperatuur (Kelvin)	-
CRI	-
Lichtsterkte (lumen) p/m	129 lm
Aantal branduren	50.000
Voltage (DC)	24V
Watt - vermogen p/m	8,3W
Lumen per Watt	14.3 lm
Watt per LED	0,02W
Bescherming	IP20, IP65 of IP67
Materiaal waterdichte bescherming (IP65/IP67)	Siliconen
Achtergrond kleur strip (PCB)	Wit
Plakstrip	IP20: 3M 300LSE
Breedte led strip	IP20: 8mm IP65: 10mm IP67: 10mm
Dikte led strip	IP20: 1,7mm IP65: 3,7mm IP67: 3,7mm
Aansluiting begin	5.5x2.1 DC stekker type vrouw
Aansluiting einde	5.5x2.1 DC stekker type man

TECHNISCHE TEKENINGEN

IP20



IP65/67



IP20



IP65




IP67





1M COB BLAUW - 384 LEDS P/M



Color Parameters:

Chromaticity Coordinate: $x=0.1558$ $y=0.0222/u'=0.2109$ $v'=0.0677$
 CCT=100000K (Duv=-0.2229) Dominant WL:Ld =452.1nm Purity=99.2%
 Ratio:R=0.4% G=8.5% B=91.2% Peak WL:Lp=447.2nm FWHM=14.7nm
 Render Index:Ra=0.2 CRI=0.1

R1 =0 R2 =0 R3 =0 R4 =0 R5 =2 R6 =0 R7 =0
 R8 =0 R9 =0 R10=0 R11=0 R12=0 R13=0 R14=0 R15=0

Photo Parameters:

Flux = 129.1 lm Eff. : 15.50 lm/W Fe = 4.316 W

Electrical parameters:

V = 23.998 V I = 0.3472 A P = 8.332 W PF = 1.000
 LEVEL:OUT WHITE:OUT

Status: Integral T = 20 ms Ip = 55049 (84%)



CE CERTIFICAAT

AN XIN TESTING CERTIFICATION

Certificate of Conformity



Certification No. : ATT20092500368E
Applicant : Ledkoning
Address : Rietveldenweg 49D
 5222AP 's Hertogenbosch, The Netherlands
Manufacturer : Ledkoning
Address : Rietveldenweg 49D
 5222AP 's Hertogenbosch, The Netherlands
Product Description : 2835 LED Strip
 24K2835-05M1220,24K2835-05M1265,30K2835-05M1220,30K2835-05M1265
 65K2835-05M1220,65K2835-05M1265,24K2835-05M2420,24K2835-05M2465
 30K2835-05M2420,30K2835-05M2465,65K2835-05M2420,65K2835-05M2465
Model : RO2835-05M1220,RO2835-05M1265,RO2835-05M2420,RO2835-05M2465
 GR2835-05M1220,GR2835-05M1265,GR2835-05M2420,GR2835-05M2465
 BL2835-05M1220,BL2835-05M1265,BL2835-05M2420,BL2835-05M2465
 OR2835-05M1220,OR2835-05M1265,OR2835-05M2420,OR2835-05M2465
Trademark : N/A

The above products have been tested by us with listed standards and found in compliance with the Directive 2014/35/EU. It is possible to use CE marking to demonstrate the compliance with this Directive.

Test Standards	EN 55015: 2019
	EN 61547: 2009
	EN 61000-3-2:2019
	EN 61000-3-3: 2013+A1:2019

The certificate is based on a single evaluation of tested samples of above-mentioned product. It does not imply an assessment of the whole production and does not permit the use of the test laboratory logo.



Authorized Signer: _____
 Kevin Liu/Manager
 Sep. 27, 2020

Shenzhen An-Xin Testing Service Co., Ltd.
 Room 402-405, Floor 4th, Building C, Yuxing Technology Industrial Park, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China
 ☎ 86-0755-23009643 📠 86-0755-23009643 🌐 <http://www.anxinlab.com/>

Adres: Rietveldenweg 49D, 5222AP 's Hertogenbosch
 Tel: +3173 704 1100
 E-mail: info@ledkoning.nl
 Website: www.ledkoning.nl